DB500® Mobile S SPECIFICATIONS





DB500 Blast Pot

- 5 Cubic Foot Capacity
- Holds 200 lb abrasive per fill
- Holds 20 gal water per fill (when wet blasting)
- 60 minute blast time per fill
- 54" H x 34" W x 40" D
- Operating Pressure: 30-150 PSI
- ASME / PED / CE Compliant
- Texas Edition: Internal parts manufactured of hardened steel
- · Lifetime Warranty on Blast Pot

"S" Trailer

- Deck Dimensions: 14' L x 5' W
- Total Trailer Dimensions:
 18'6" L x 6'6" W
- · Purpose Built Heavy Duty Trailer
- DOT Compliant LED Lights
- Two 6000 lb Axles
- Dual Axle Electric Brakes
- Electric Breakaway System
- 8 Ply Tires + Full Size Spare
- 4,320 lb Dry Weight

185 CFM Compressor

- Powered by Kohler
- 49 Horsepower Engine
- 23 Gallon Diesel Tank
- Fuel Consumption:1.5 gal/hr @ 60%
- Open-canopy design with spin-on oil and separator filters for ease of maintenance
- Ultra Silent Tier 4 FINAL
- Extended Warranty on Air Compressors (5 years on compressor, 3 years on engine)

Included Accessories

- 100 ft Blast Hose
- Electric Deadman for instant on/off
- Tungsten Carbide Nozzle (SLV #5)
- · Fill Funnel with Screen
- 150 Gallon Water Tank
- 48 GPM Water Pump
- ADCS-350 Air Dryer / Cooler which allows for dry blasting and soda blasting, in addition to Dustless Blasting