

# GOODRIDE TIRES



## OFFERING & SPECIFICATIONS

- » Thick construction provides for reliable towing and braking
- » Double steel belt construction to counteract heat cycle damage, expanding and contracting, and provide towing stability under load
- » Puncture resistant with full nylon cap construction
- » Heatless compound technology to slow down the aging of the tire and extend life
- » Tread depth provides low rolling resistance reducing tread wear and improving fuel economy
- » 6 Year Warranty and 1 Year, Hassle-Free Replacement
- » Dexter Defender Roadside Assistance

Size	Load Range	Ply Rating	Load Capacity		Speed Rating	Tread Depth	*Tire Construction	
			Single	Dual			Sidewall	Tread
ST145R12	E	10	1520 lbs/80 psi	N/A	M (81 mph)	7/32"	2P	2P+2S+1N
ST175/80R13	C	6	1360 lbs/50 psi	N/A	M (81 mph)	8/32"	1A	1A+2S+1N
ST175/80R13	D	8	1615 lbs/65 psi	N/A	M (81 mph)	8/32"	2A	2A+2S+1N
ST185/80R13	D	8	1760 lbs/65 psi	N/A	M (81 mph)	8/32"	2A	2A+2S+1N
ST205/75R14	C	6	1760 lbs/50 psi	N/A	M (81 mph)	8/32"	1A	1A+2S+1N
ST205/75R14	D	8	2040 lbs/65 psi	N/A	M (81 mph)	8/32"	2A	2A+2S+1N
ST205/75R15	C	6	1820 lbs/50 psi	N/A	M (81 mph)	8/32"	1A	1A+2S+1N
ST205/75R15	D	8	2150 lbs/65 psi	N/A	M (81 mph)	8/32"	2A	2A+2S+1N
ST225/75R15	D	8	2540 lbs/65 psi	N/A	M (81 mph)	9/32"	2P	2P+2S+1N
ST225/75R15	E	10	2830 lbs/80 psi	N/A	M (81 mph)	9/32"	2P	2P+2S+1N
ST235/80R16	E	10	3520 lbs/80 psi	3080 lbs/80 psi	M (81 mph)	9/32"	2P	2P+2S+1N
ST235/85R16	F	12	3960 lbs/95 psi	3520 lbs/95 psi	M (81 mph)	9/32"	2P	2P+2S+1N
ST235/80R16	G	14	4080 lbs/110 psi	3640 lbs/110 psi	L (75 mph)	9/32"	1S	4S
ST235/85R16	G	14	4400 lbs/110 psi	3860 lbs/110 psi	L (75 mph)	10/32"	1S	4S
215/75R17.5	H	16	4850 lbs/123 psi	4540 lbs/123 psi	L (75 mph)	12/32"	1S	4S
235/75R17.5	J	18	6005 lbs/128 psi	5675 lbs/128 psi	L (75 mph)	13/32"	1S	4S

\*Tire Construction Abbreviations: A = Polyamide; P = Polyester; S = Steel; N = Nylon

[www.dexteraxle.com](http://www.dexteraxle.com)

© 2005-2013 Dexter Axle Company | 11E-11P-001 | 2013181

